



ZL30-II:

- YTO LR6B3-22 engine, more powerful and low fuel consumption.
- Whole-hydraulic steering device, operating lightly and small steering radius.
- More optional accessory working implements: Joy-stick control, Log Clamp, ROPS Frame, air conditioner for cabin.
- Whole machine has high performance and cost ratio.

ZL50D-II:

- Styer technology Wechai engine, more powerful and low fuel consumption, CUMMINS or SHANGHAI D6114 is optional.
- Power-shift gearbox and single-stage 4-element hydraulic torque converter, which can automatically adjust the output torque.
- More optional accessory working implements: Joy-stick control, Log Clamp, ROPS Frame, air conditioner for cabin.
- Whole machine has high performance and cost ratio.

Model	ZL30- II		Model	ZL50D- II	
Total weight	kg	9950	Total weight	kg	16500
Bucket capacity	m ³	1.7	Bucket capacity	m ³	3
Rated load	kg	3000	Rated load	kg	5000
Movable arm liftig time	s	≤6.5	Movable arm liftig time	s	≤6.5
Three item time	s	≤12	Three item time	s	≤11.8
Min turning radius	mm	5022	Min turning radius	mm	5900
Forward 1-4 gear	km/h	6.5-36	Forward 1-2 gear	km/h	11.5-36
Reverse 1-2 gear	km/h	7.5-23	Reverse	km/h	0-16
Dumping clearance	mm	3050	Dumping clearance	mm	3050
Dumping reach	mm	974	Dumping reach	mm	1290
Overall dimension(L x W x H)	mm	7105 x 2400 x 3080	Overall dimension(L x W x H)	mm	7500 x 2835 x 3400
Engine model	LR6B3-22		Engine model	WD10G220E21	
Engine rated power	kW	92	Engine rated power	kW	162
Fuel tank capacity	L	150	Fuel tank capacity	L	220